



XE 5738

Architectural Coating

Architectural Coating

GT Products XE 5738 is a odorless reactive siloxane polymer emulsion designed for architectural coating applications to impart water repellency and stain resistance.

Typical Properties:

Diluent :	Water.
Solids Content:	12 -16 %
Color:	Off White
Specific Gravity:	0.99 (Approximately)
Emulsification Type:	Cationic
Viscosity:	Brookfield viscosity #1@100 = 20 cs
Ph Level:	8 -11

Application:

XE 5738 is a one component system designed to be used as received. When coating substrates with varying degrees of absorption, it is recommended that a light second coat be applied.

Each user bears the full responsibility for making its own determination as to the suitability of Supplier's materials, products, services, recommendations or advice for its own particular purpose. Each user must identify and perform tests and analyses sufficient to assure it that its finished parts will be safe and suitable for use under end-use conditions. Because actual use of products by the user is beyond the control of Supplier, such use is within the exclusive responsibility of the user, and Supplier cannot be held responsible for any loss incurred through incorrect or faulty use of the products. Further, no statement contained herein concerning a possible or suggested use of any material, product, service or design is intended or should be construed to grant any license under any patent or other intellectual property right of Supplier or any of its subsidiaries or affiliated companies, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

GT Products inc. 501 Industrial Blvd. Grapevine, TX 76051 Phone # 800-221-0866 Fax # 817- 421-1211