

GT Products, Inc.
MATERIAL SAFETY DATA SHEET

PRODUCT

GT Products® 6166 - Base

1. PRODUCT AND COMPANY IDENTIFICATION

Manufactured by:

GT Products, Inc.
501 Industrial Blvd.
Grapevine, TX 76051

Telephone: (817) 481-7113

Fax: (817) 421-1211

EMERGENCY (Chemtrec): 800-424-9300

Date prepared: 03/09/10

by: Daniel Shaw

Chemical Type /Description:

Silicone Rubber Base

2. HAZARDOUS INGREDIENTS

<u>Component</u>	<u>Approximate %</u>	<u>TLV/PEL</u>	<u>CAS Number</u>
------------------	----------------------	----------------	-------------------

None

This product contains Methylpolysiloxanes, which can generate Formaldehyde at approximately 300F (150C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin, eye, and throat irritant, is toxic and a potential cancer hazard.

HMIS RATING:

FLAMMABILITY: 1

REACTIVITY: 0

HEALTH: 1

3. EFFECTS OF EXPOSURE

Potential Health Effects:

Ingestion: Very low toxicity expected, a likely laxative.

Skin Contact: None expected.

Inhalation: None expected due to very low vapor pressure.

Eye Contact: May irritate.

4. FIRST AID MEASURES

Ingestion: Seek medical attention if adverse symptoms noted.

Skin: Remove with dry towel, then wash with soap and water.

Eyes: Rinse 15 minutes with running water. Seek medical attention if irritation persists.

Inhalation: Seek fresh air if needed.

Other: Not applicable.

5. FIRE FIGHTING INFORMATION

Flash Point (Method): >205F Setaflash

Flammability Class: None.

Flammability Limits in Air: Not available.

GT Products

Extinguishing Media: All standard media for chemical fires.
Hazardous Combustion Products CO, CO₂, SiO₂, H₂CO
Special Fire Fighting Notes: Like all silicones, GT Products® GT 6166 Base can produce formaldehyde when strongly heated in air.

6. ACCIDENTAL RELEASE MEASURES

Pick up spilled material with absorbent clay, then wash area thoroughly with water and detergent. Spilled material is very slippery.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes and prolonged skin contact.
Storage: Store in cool (<40C) closed and dry containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Good general ventilation.

Personal Protective Equipment

Eyes: Safety glasses.
Skin: Rubber or plastic gloves as desired.
Inhalation: Not normally required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Flowable paste.
Color: Translucent off-white.
Odor: Very slight.
Boiling Point: Will not boil.
Vapor Density (air = 1): There is negligible vapor pressure.
Specific Gravity: 1.1
Solubility in Water: None.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.
Hazardous Polymerization: Will not occur.
Decomposition Products: Only in fire conditions, see section 5.
Materials to Avoid: None.
Conditions to Avoid: None – keep tightly sealed to avoid contamination.

11. TOXICOLOGICAL INFORMATION

See section 3.

GT Products

12. ECOLOGICAL INFORMATION

None available.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with state and local regulations. The preferred method is to cure with the appropriate curing agent (C6166) and discard the cured rubber in a sanitary landfill.

14. TRANSPORT INFORMATION

DOT SHIPPING NAME: Not regulated.
DOT HAZARD CLASS: None.
UN/NA Number: None.

15. REGULATORY INFORMATION

TSCA INVENTORY STATUS: Listed.

SARA TITLE III / CERCLA

SECTION 302 EXTREMELY TOXIC: None.

SECTION 304 CERCLA HAZARD: None.

SECTION 311 / 312 HAZARD None.

CLASS:

SECTION 313 TOXIC CHEMICALS: None.

16. OTHER INFORMATION

We believe the above information is correct as of the date of this data sheet. However, as this information and the conditions under which the product are used are beyond the control of GT PRODUCTS, INC., it is the user's obligation to determine the conditions for the safe use of the product. No warranty, expressed or implied, is hereby made.

GT Products, Inc.
MATERIAL SAFETY DATA SHEET

PRODUCT

GT Products® CAT-6166

1. PRODUCT AND COMPANY IDENTIFICATION

Manufactured by:

GT Products, Inc.
501 Industrial Blvd.
Grapevine, TX 76051

Telephone: (817) 481-7113
Fax: (817) 421-1211
EMERGENCY (Chemtrec): (800) 424-9300

Date prepared: 03/09/10

by: Daniel Shaw

Chemical Type /Description:

Silicone Rubber Curing Agent (Hardener)

2. HAZARDOUS INGREDIENTS

<u>Component</u>	<u>Approximate %</u>	<u>TLV/PEL</u>	<u>CAS Number</u>
------------------	----------------------	----------------	-------------------

None

This product contains Methylpolysiloxanes, which can generate Formaldehyde at approximately 300F (150C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin, eye, and throat irritant, is toxic and a potential cancer hazard.

HMIS RATING:

FLAMMABILITY: 1

REACTIVITY: 1

HEALTH: 1

3. EFFECTS OF EXPOSURE

Potential Health Effects:

Ingestion: Low toxicity expected, a likely laxative.
Skin Contact: May cause contact dermatitis on long exposure.
Inhalation: Not a significant route of entry due to low vapor pressure.
Eye Contact: May irritate.

4. FIRST AID MEASURES

Ingestion: Seek medical attention if adverse symptoms develop.
Skin: Remove with dry towel, then wash with soap and water.
Eyes: Rinse 15 minutes with running water. Seek medical attention if irritation persists.
Inhalation: Seek fresh air if needed.
Other: NA

5. FIRE FIGHTING INFORMATION

Flash Point (Method): >205F Setaflash

Flammability Class: None

GT Products

Flammability Limits in Air:	Not available
Extinguishing Media:	All standard media for chemical fires.
Hazardous Combustion Products	CO, CO ₂ , SiO ₂ , H ₂ , H ₂ CO
Special Fire Fighting Notes:	Like all silicones, GT Products® GT 6166 - CAT can produce formaldehyde when strongly heated in air. Additionally, GT Products® GT 6166 - CAT contains silicone hydrides that can be decomposed by high heat to hydrogen gas.

6. ACCIDENTAL RELEASE MEASURES

Pick up spilled material with absorbent clay, then wash area thoroughly with water and detergent. Spilled material is very slippery.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes and prolonged skin contact.
Storage: Store in cool (<40C) closed and dry containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Good general ventilation.
Personal Protective Equipment
Eyes: Safety glasses.
Skin: Rubber or plastic gloves as desired.
Inhalation: Not normally required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Clear moderate viscosity liquid.
Color: Colorless.
Odor: Very slight.
Boiling Point: >180C (decomposes – does not boil).
Vapor Density (air = 1): >10, but vapor pressure is very low.
Specific Gravity: 1.0
Solubility in Water: Negligible.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable in the absence of contamination.
Hazardous Polymerization: Will not occur.
Decomposition Products: Only in fire conditions or when contaminated see section 5 and below.
Materials to Avoid: Bases, oxidizing agents.

GT Products

Conditions to Avoid: None – keep tightly sealed to avoid contamination. This material contains silicone hydrides. In contact with acids, bases (particularly) or oxidizing agents, GT Products® GT 6166 - CAT can release hydrogen gas as the silicone hydrides react with the contaminants. Storage in the original container, in a cool dry place will avoid problems.

11. TOXICOLOGICAL INFORMATION

See section 3.

12. ECOLOGICAL INFORMATION

None available.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with state and local regulations.

14. TRANSPORT INFORMATION

DOT SHIPPING NAME: Not regulated.

DOT HAZARD CLASS: None.

UN/NA Number: None.

15. REGULATORY INFORMATION

TSCA INVENTORY STATUS: Listed

SARA TITTLE III / CERCLA

SECTION 302 EXTREMELY TOXIC: None.

SECTION 304 CERCLA HAZARD: None.

SECTION 311 / 312 HAZARD

CLASS:

SECTION 313 TOXIC CHEMICALS: None.

16. OTHER INFORMATION

We believe the above information is correct as of the date of this data sheet. However, as this information and the conditions under which the product are used are beyond the control of GT PRODUCTS, INC., it is the user's obligation to determine the conditions for the safe use of the product. No warranty, expressed or implied, is hereby made.